



[Knowledge Base](#) > [Audio, Call Quality and Network Search](#) > [Troubleshooting](#) > [Heartbeat](#)

## Heartbeat


Santiago Garcia - 2026-02-18 - [Troubleshooting](#)

## Heartbeat

Heartbeat provides a basic ICMP report about potential issues at the customers network. Its usefulness is a guide only, Heartbeat is less helpful for monitoring momentary or sudden packet loss, unless those outages are consistent over periods longer than five minutes. In summary Heartbeat is a useful overview of the customers connectivity between our two networks.

### Enabling Heartbeat

1. Select Tools > Heartbeat.
2. Select Preferences
3. Enabling ICMP - Generic Instruction



### Heart requires ICMP to be configured on the customer router.

1. Access your router's admin interface. This is typically done by entering your router's IP address in a web browser. The address is usually 192.168.1.1 or 192.168.0.1.

2. Log in with the admin username and password. These are often defaulted to "admin/admin" or "admin/password" if you haven't changed them. Check your router documentation.
3. Find the firewall or security settings. This may be under a "Firewall", "Security" or "Access Control" menu.
4. Look for a setting to enable ICMP or ping responses. Many routers have a checkbox to "Allow ICMP" or "Respond to ping". Make sure this is enabled.
5. If you don't see an explicit ICMP or ping setting, you may need to create a basic firewall rule to allow ICMP traffic. Add a rule to allow "ICMP" or "ICMP Echo" on the WAN interface.
6. Save your changes. You may need to reboot the router for changes to fully take effect.